

HR 1255W

HR Series

Document P62 | Page 1/1



PUBLISHED MODEL DATA

Nominal voltage	12 V
Rated capacity	14 Ah
Dimensions (L x W x H)	151 x 99 x 95 mm
Total height	100 mm
Terminal	F1/F2/M5

PRODUCT OVERVIEW

Capacity range: 21W to 510W/cell(25°C). Voltage range: 12V.

PUBLISHED PRODUCT HIGHLIGHTS

- High-tin multi-element alloy grids and special lead paste formulations enhance the corrosion resistance of the grids, extend the battery life and improve the high-current discharge capability
- 3D-structured grids have a larger surface area, which is conducive to the optimization design for high-current conduction and the adhesion of active materials
- CCDD grids (stamped grids) are characterized by high density, strong corrosion resistance and good consistency

APPLICATIONS

IDC (Internet Data Center) Data Centers | Uninterruptible Power Supply Systems (UPS)

ORDERING AND DOCUMENT CONTROL NOTE

Product appearance, terminal configuration and dimensional tolerances may vary by order. Request the current approved MSDS/SDS, certification scope, complete discharge data or quotation when required.

DIRECT GLOBAL SALES - Song Yang

Email: yhc240110@gmail.com

WhatsApp: +86 166 3191 9138

Website: tianyipowerglobal.com

Request controlled technical documents

Published product information - confirm the final approved specification before ordering.

Product selection reference only - not a quotation, warranty, test report, certificate or MSDS/SDS.

P62 / 1