TG 12V65Ah

TG Series

PUBLISHED MODEL DATA

Nominal voltage	**12 V**
Rated capacity	**65 Ah**
Dimensions (L x W x H)	**350 x 167 x 174 mm**
Terminal	**M8**
Published dimension tolerance	**+/-3 mm**

PRODUCT OVERVIEW

Gel batteries are an innovative battery technology that combines the high performance of traditional lead-acid batteries with the stability and safety of advanced gel electrolyte technology. By introducing special gel additives into the electrolyte, this...

PUBLISHED PRODUCT HIGHLIGHTS

- High-tin multi-element alloy grids and special lead paste formulations improve the corrosion resistance of the grids
- Nano-silica gel electrolyte solves the problem of electrolyte stratification and extends the battery's cycle life
- With a large heat capacity, it reduces the risk of thermal runaway, is less likely to dry out, and can be used in relatively harsh environments

APPLICATIONS

Energy storage for new energy | Hybrid oil-electricity solutions | Uninterruptible Power Supply Systems (UPS) | Peak load regulation for electric power | Communications | Subways, etc.

ORDERING AND DOCUMENT CONTROL NOTE

Product appearance, terminal configuration and dimensional tolerances may vary by order. Request the current approved MSDS/SDS, certification scope, complete discharge data or quotation when required.

DIRECT GLOBAL SALES - Song Yang

Email: yhc240110@gmail.com

WhatsApp: +86 166 3191 9138

Website: tianyipowerglobal.com

Request controlled technical documents

Published product information - confirm the final approved specification before ordering.
Product selection reference only - not a quotation, warranty, test report, certificate or MSDS/SDS.